

Docket No. ALG10NP



Mail Label No. EF103846781US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Sercel et al

Filed: 02/16/2001

App. No.: 09/788,301

For: Resonant optical power control device assemblies

PRELIMINARY AMENDMENT UNDER 37 CFR §1.115

Assistant Commissioner for Patents  
Washington, DC 20231

07/30/2001

Sir:

Please amend the above named application as set forth below.

AMENDMENT

Please insert the following new claims.

13. In a resonant optical modulator assembly, the assembly comprising
- an alignment member,
  - a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned on and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide at the evanescent optical coupling segment thereof, and
  - an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the optical resonator,
- the improvement comprising:
- a waveguide-alignment groove provided in the alignment member for receiving the transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the optical resonator therein,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the evanescent optical coupling segment of the transmission optical waveguide.

14. In a resonant optical modulator assembly, the assembly comprising an alignment member,

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,

an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned on and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide at the evanescent optical coupling segment thereof, and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned on and secured to the alignment member so as to be evanescently optically coupled to the optical resonator,

the improvement comprising:

a waveguide-alignment groove provided in the alignment member for receiving the transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the optical resonator therein,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the evanescent optical coupling segment of the transmission optical waveguide,

the resonator-alignment groove and the modulator being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the optical modulator.

15. In a resonant optical modulator assembly, the assembly comprising
- an alignment member,
  - a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - multiple optical resonators, each of the multiple optical resonators supporting at least one corresponding resonant optical mode, the multiple optical resonators being positioned on and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide at the evanescent optical coupling segment thereof; and
  - multiple optical modulators, each positioned so as to be evanescently optically coupled to a corresponding optical resonator, for modulating, in response to an applied control signal, corresponding coupling conditions between the transmission optical waveguide and the corresponding optical resonators, in turn enabling controlled modulation of a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode carrying the optical signal is substantially resonant with at least one of the corresponding resonant optical modes,
- the improvement comprising:
- a waveguide-alignment groove provided in the alignment member for receiving the transmission optical waveguide therein; and
  - multiple resonator-alignment grooves, each provided in the alignment member for receiving a corresponding optical resonator therein,
- the waveguide-alignment groove and the multiple resonator-alignment grooves being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the multiple optical resonators and the evanescent optical coupling segment of the transmission optical waveguide.

16. In a resonant optical modulator assembly, the assembly comprising  
an alignment member,  
a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal  
carried by a waveguide optical mode, the transmission fiber-optic waveguide being  
positioned on and secured to the alignment member and having an evanescent optical  
coupling segment,  
an optical resonator for supporting at least one resonant optical mode, the optical resonator  
being positioned on and secured to the alignment member so as to be evanescently  
optically coupled to the transmission fiber-optic waveguide at the evanescent optical  
coupling segment thereof, and  
an optical modulator for modulating, in response to an applied control signal, a coupling  
condition between the transmission fiber-optic waveguide and the optical resonator so  
as to controllably modulate a level of transmission through the transmission fiber-optic  
waveguide of the optical signal when the waveguide optical mode is substantially  
resonant with at least one of the resonant optical modes, the optical modulator being  
positioned so as to be evanescently optically coupled to the optical resonator,  
the improvement comprising:  
a waveguide-alignment groove provided in the alignment member for receiving the  
transmission fiber-optic waveguide therein; and  
a resonator-alignment groove provided in the alignment member for receiving the optical  
resonator therein,  
the waveguide-alignment groove and the resonator-alignment groove being positioned on  
the alignment member so as to substantially reproducibly establish and substantially  
stably maintain evanescent optical coupling between the optical resonator and the  
evanescent optical coupling segment of the transmission fiber-optic waveguide.
17. A resonant optical modulator assembly, comprising:  
an alignment member, the alignment member including a waveguide-alignment groove and  
a resonator-alignment groove;  
a polarization-preserving transmission fiber-optic waveguide adapted for transmitting  
therethrough an optical signal carried by a waveguide optical mode, the transmission  
fiber-optic waveguide being positioned within the waveguide-alignment groove and  
secured to the alignment member and having an evanescent optical coupling segment;

an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the evanescent optical coupling segment thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the optical resonator, the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the evanescent optical coupling segment of the transmission fiber-optic waveguide.

18. In a resonant optical modulator assembly, the assembly comprising
- an alignment member,
- a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission fiber-optic waveguide being positioned on and secured to the alignment member and having a fiber-optic-taper segment,
- an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned on and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof, and
- an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the optical resonator,
- the improvement comprising:

a waveguide-alignment groove provided in the alignment member for receiving the transmission fiber-optic waveguide therein; and  
a resonator-alignment groove provided in the alignment member for receiving the optical resonator therein,  
the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the fiber-optic-taper segment of the transmission optical waveguide.

19. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;  
a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission fiber-optic waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a side-etched evanescent optical coupling segment;  
an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the side-etched evanescent optical coupling segment thereof; and  
an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the optical resonator,  
the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the side-etched evanescent optical coupling segment of the transmission fiber-optic waveguide.

20. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and the evanescent optical coupling segment of the transmission optical waveguide.

21. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being

positioned within the waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator fiber being provided with a delocalized-optical-mode suppressor on at least one of the first and second segments of the resonator optical fiber, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and the evanescent optical coupling segment of the transmission optical waveguide.

22. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;



a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator fiber being provided with a hermetic carbon delocalized-optical-mode suppressor on at least one of the first and second segments of the resonator optical fiber, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and the evanescent optical coupling segment of the transmission optical waveguide.

23. A resonant optical modulator assembly, comprising:

- an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;
- a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission fiber-optic waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;
- a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical

fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being provided with a taper-positioning-and-support member, the taper-positioning-and-support member being adapted for engaging the fiber-optic-taper segment in proximity to the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to evanescently optically couple the fiber-ring optical resonator and the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof and so as to engage the fiber-optic-taper segment and the taper-positioning-and-support member; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member and the taper-positioning-and-support member being positioned on the resonator optical fiber so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and the fiber-optic-taper segment of the transmission fiber-optic waveguide.

24. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission fiber-optic waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being provided with a taper-positioning-and-support member, the taper-positioning-and-support member being adapted for engaging the fiber-optic-taper segment in proximity to the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to evanescently optically couple the fiber-ring optical resonator and the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof and so as to engage the fiber-optic-taper segment and the taper-positioning-and-support member; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member and the taper-positioning-and-support member being positioned on the resonator optical fiber so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and the fiber-optic-taper segment of the transmission fiber-optic waveguide, the taper-positioning-and-support member being positioned on the resonator optical fiber so as to position the fiber-optic-taper segment at a location axially displaced from an axial midpoint of the fiber-ring optical resonator, thereby substantially reducing undesirable taper-induced optical loss of the fiber-ring optical resonator.

25. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission fiber-optic waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof.

26. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being

positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof,

a desired length of an elongated region of evanescent optical coupling provided by partially wrapping the fiber-optic-taper segment around the fiber-ring optical resonator being determined by a desired level of evanescent optical coupling between the fiber-ring resonator and the fiber-optic-taper segment,

arrangement of the waveguide-alignment groove and the resonator-alignment groove on the alignment member being determined by the desired length of the elongated region of evanescent optical coupling.

27. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove, a resonator-alignment groove, and a pair of taper-segment-support members, the taper-segment-support members being positioned on the alignment member with the resonator groove therebetween;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove, the resonator-alignment groove, and the taper-segment-support members being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof and engaged with the taper-segment-support members.

28. A resonant optical modulator assembly, comprising:

- an alignment member, the alignment member including a waveguide-alignment groove, a resonator-alignment groove, and a pair of taper-segment-support grooves, the taper-segment-support grooves being positioned on the alignment member with the resonator groove therebetween;
- a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;
- a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and
- a pair of taper-segment-support fibers, the taper-segment-support fibers being respectively positioned within the pair of taper-segment-support grooves and secured to the alignment member, each taper-segment-support fiber including a taper-support segment integral with the taper-segment-support fiber between adjacent segments of the taper-segment-support fiber, the taper-segment-support fibers being positioned so as to support the fiber-optic-taper segment on the respective fiber-taper-support segments; and
- an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the

optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove, the resonator-alignment groove, and the taper-segment-support grooves being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof and engaged with the taper-segment-support segments.

29. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove, a resonator-alignment groove, and a pair of taper-segment-support grooves, the taper-segment-support grooves being positioned on the alignment member with the resonator groove therebetween;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

a pair of taper-segment-support fibers, the taper-segment-support fibers being respectively positioned within the pair of taper-segment-support grooves and secured to the alignment member, each taper-segment-support fiber including a taper-support segment integral with the taper-segment-support fiber between adjacent segments of the taper-segment-support fiber, the taper-segment-support fibers being positioned so as to



support the fiber-optic-taper segment on the respective fiber-taper-support segments;  
and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,  
the waveguide-alignment groove, the resonator-alignment groove, and the taper-segment-support grooves being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof and engaged with the taper-segment-support segments, the taper-segment-support segment including paired axially-juxtaposed radially-extending radially-tapered transverse flanges, the fiber-optic-taper segment resting on the paired flanges..

30. A resonant optical modulator assembly, comprising:

- an alignment member, the alignment member including a waveguide-alignment groove, a resonator-alignment groove, and a pair of taper-segment-support grooves, the taper-segment-support grooves being positioned on the alignment member with the resonator groove therebetween;
- a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;
- a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential

surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

a pair of taper-segment-support fibers, the taper-segment-support fibers being respectively positioned within the pair of taper-segment-support grooves and secured to the alignment member, each taper-segment-support fiber including a taper-support segment integral with the taper-segment-support fiber between adjacent segments of the taper-segment-support fiber, the taper-segment-support fibers being positioned so as to support the fiber-optic-taper segment on the respective fiber-taper-support segments, each taper-segment-support fiber being provided with a de-localized-optical-mode suppressor on at least one of the adjacent segments thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove, the resonator-alignment groove, and the taper-segment-support grooves being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof and engaged with the taper-segment-support segments.

31. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove, a resonator-alignment groove, and a pair of taper-segment-support grooves, the taper-segment-support grooves being positioned on the alignment member with the resonator groove therebetween;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission fiber-optic waveguide at the fiber-optic-taper segment thereof; and

a pair of taper-segment-support fibers, the taper-segment-support fibers being respectively positioned within the pair of taper-segment-support grooves and secured to the alignment member, each taper-segment-support fiber including a taper-support segment integral with the taper-segment-support fiber between adjacent segments of the taper-segment-support fiber, the taper-segment-support fibers being positioned so as to support the fiber-optic-taper segment on the respective fiber-taper-support segments, each taper-segment-support fiber being provided with a hermetic carbon coating de-localized-optical-mode suppressor on at least one of the adjacent segments thereof; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission fiber-optic waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove, the resonator-alignment groove, and the taper-segment-support grooves being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the fiber-ring optical resonator near a portion of the outer circumference thereof and engaged with the taper-segment-support segments.

32. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and multiple resonator-alignment grooves;

a transmission fiber-optic waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having a fiber-optic taper segment;

multiple fiber-ring optical resonators, each formed on a corresponding resonator optical fiber, each fiber-ring optical resonator including a transverse resonator segment integral with the corresponding resonator optical fiber between first and second segments of the corresponding resonator optical fiber, each resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the corresponding resonator optical fiber so as to enable the resonator segment to support at least one corresponding resonant optical mode near an outer circumferential surface of the resonator segment, each resonator optical fiber being positioned within a corresponding one of the multiple resonator-alignment grooves and secured to the alignment member so as to be evanescently optically coupled to the fiber-optic taper segment of the transmission fiber-optic waveguide; and

multiple optical modulators for modulating, in response to a corresponding applied control signal, a coupling condition between the transmission fiber-optic waveguide and a corresponding one of the multiple fiber-ring optical resonators so as to controllably modulate a level of transmission through the transmission fiber-optic waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the corresponding resonant optical modes, each optical modulator being positioned so as to be evanescently optically coupled to the corresponding fiber-ring optical resonator,

the waveguide-alignment groove and the multiple resonator-alignment grooves being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the multiple fiber-ring optical resonators near portions of the outer circumferences thereof.

33. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being positioned within the waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

a fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide; and

an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the fiber-ring optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being provided on the resonator fiber and positioned so as to be evanescently optically coupled to the fiber-ring optical resonator,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the fiber-ring optical resonator and evanescent optical coupling segment of the transmission optical waveguide.

34. A resonant optical modulator assembly, comprising:

an alignment member, the alignment member including a waveguide-alignment groove and a resonator-alignment groove;

a transmission optical waveguide adapted for transmitting therethrough an optical signal carried by a waveguide optical mode, the transmission optical waveguide being

- positioned within the waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
- an optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the transmission optical waveguide at the evanescent optical coupling segment thereof; and
- an optical modulator for modulating, in response to an applied control signal, a coupling condition between the transmission optical waveguide and the optical resonator so as to controllably modulate a level of transmission through the transmission optical waveguide of the optical signal when the waveguide optical mode is substantially resonant with at least one of the resonant optical modes, the optical modulator being positioned so as to be evanescently optically coupled to the optical resonator,
- the alignment member comprising
- a first alignment substrate including the waveguide-alignment groove thereon, and
  - a second alignment substrate positioned on and secured to the first alignment substrate, the second alignment substrate including at least one of the resonator-alignment groove thereon and the optical modulator positioned thereon and secured thereto,
- the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the transmission optical waveguide and the optical resonator,
- the resonator-alignment groove and the modulator being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the optical modulator.
35. A method for assembling a resonant optical modulator assembly, comprising the steps of:
- positioning a transmission optical waveguide within a waveguide-alignment groove of an alignment member and securing the transmission optical waveguide to the alignment member;
  - positioning an optical resonator within a resonator-alignment groove of the alignment member, so that the optical resonator is evanescently optically coupled to an evanescent optical coupling segment of the transmission optical waveguide, and securing the optical resonator to the alignment member; and

positioning an optical modulator on the alignment member, so that the optical modulator is evanescently optically coupled to the optical resonator, and securing the optical modulator to the alignment member,

the waveguide-alignment groove and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the optical resonator and the evanescent optical coupling segment of the transmission optical waveguide.

36. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member,
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially

remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough, the improvement comprising:

- a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;
- a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and
- a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

37. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member,
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof, and



- an optical modulator for modulating, in response to an applied control signal, a coupling condition between at least one of the first and second transmission optical waveguides and the resonant optical assembly, the optical modulator being positioned so as to be evanescently optically coupled to the resonant optical assembly,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- the optical modulator being adapted for enabling transfer of a resonant optical signal to be disabled in response to an applied disabling control signal and re-enabled in response to an applied enabling control signal,
- the improvement comprising:
- a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;
  - a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and
  - a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,
- the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.
38. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member,

- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and
- a single optical resonator for supporting at least one resonant optical mode, the optical resonator being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- the improvement comprising:
- a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;
- a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and
- a resonator-alignment groove provided in the alignment member for receiving the optical resonator therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the optical resonator and between the second transmission optical waveguide and the optical resonator.

39. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member,
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and
  - a coupled-resonator optical assembly, the coupled-resonator optical assembly supporting resonant optical modes and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the improvement comprising:

- a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;
  - a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and
  - a resonator-alignment groove provided in the alignment member for receiving the coupled-resonator optical assembly therein,
- the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the coupled-resonator optical assembly and between the second transmission optical waveguide and the coupled-resonator optical assembly.

40. In an optical slicer/interleaver assembly for an optical WDM system, the assembly comprising
- an alignment member,
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

multiple optical signals entering the optical slicer/interleaver assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the optical slicer/interleaver assembly therethrough,

multiple optical signals entering the optical slicer/interleaver assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the optical slicer/interleaver assembly therethrough,

the improvement comprising:

a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;

a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

41. In an optical channel add/drop filter assembly for an optical WDM system, the assembly comprising

an alignment member,

a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,

a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the optical channel add/drop filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the optical channel add/drop filter assembly therethrough,

multiple optical signals entering the optical channel add/drop filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the optical channel add/drop filter assembly therethrough,

the improvement comprising:

a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;

a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical

assembly and between the second transmission optical waveguide and the resonant optical assembly.

42. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member;
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and
- a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide,
- the improvement comprising:

a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;

a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

43. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the



- second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly,
- at least one of the first transmission optical waveguide and the second transmission optical waveguide being a polarization-preserving fiber-optic waveguide.
44. In a resonant optical filter assembly for an optical WDM system, the assembly comprising an alignment member,
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment,
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned on and secured to the alignment member and having an evanescent optical coupling segment, and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned on and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide,

the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment,

the improvement comprising:

a first waveguide-alignment groove provided in the alignment member for receiving the first transmission optical waveguide therein;

a second waveguide-alignment groove provided in the alignment member for receiving the second transmission optical waveguide therein; and

a resonator-alignment groove provided in the alignment member for receiving the resonant optical assembly therein,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

45. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a fiber-optic waveguide,

the evanescent optical coupling segment of the transmission fiber-optic waveguide being a side-etched fiber-optic segment.

46. A resonant optical filter assembly for an optical WDM system, comprising:

an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;

a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

47. A resonant optical filter assembly for an optical WDM system, comprising:

an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;  
a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide

- optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
- a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the

resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator fiber being provided with a delocalized-optical-mode suppressor on at least one of the first and second segments of the resonator optical fiber, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

48. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the

second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator fiber being provided with a hermetic carbon coating delocalized-optical-mode suppressor on at least one of the first and second segments of the resonator optical fiber, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

49. A resonant optical filter assembly for an optical WDM system, comprising:



- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
- a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being provided with a taper-positioning-and-support member for engaging the fiber-optic-taper segment in proximity to the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

50. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
- a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
- at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment,
- the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one

resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being provided with a taper-positioning-and-support member for engaging the fiber-optic-taper segment in proximity to the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly,

the taper-positioning-and-support member being positioned on the resonator optical fiber so as to position the fiber-optic-taper segment at a location axially displaced from an axial midpoint of the at least one fiber-ring optical resonator, thereby substantially reducing undesirable taper-induced optical loss of the at least one fiber-ring optical resonator.

51. A resonant optical filter assembly for an optical WDM system, comprising:

- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
- a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
- a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-

optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof.

52. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially

remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof,

a desired length of an elongated region of evanescent optical coupling provided by partially wrapping the fiber-optic-taper segment around the fiber-ring optical resonator being determined by a desired level of evanescent optical coupling between the fiber-ring optical resonator and the fiber-optic-taper segment,

arrangement of the waveguide-alignment groove and the resonator-alignment groove on the alignment member being determined by the desired length of the elongated region of evanescent optical coupling.

53. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide

optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;

a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the



resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides, at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof, the alignment member further including a pair of taper-segment-support members for engaging the fiber-optic-taper segment and holding the fiber-optic-taper segment partially wrapped around the at least one fiber-ring optical resonator, the taper-segment-support members being positioned on the alignment member with the resonator-alignment groove therebetween.

54. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and

a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-

optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof,  
the alignment member further including a pair of taper-segment-support fibers for engaging the fiber-optic-taper segment and holding the fiber-optic-taper segment partially wrapped around the at least one fiber-ring optical resonator, the taper-segment-support fibers being positioned on the alignment member in corresponding taper-segment-support-fiber grooves thereof with the resonator-alignment groove therebetween,  
each taper-segment-support fiber comprising a transverse taper-segment-support segment integral with the taper-segment-support fiber between adjacent support-fiber segments, the fiber-optic-taper segment being supported by an outer circumference of the taper-segment-support segment.

55. A resonant optical filter assembly for an optical WDM system, comprising:  
an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;  
a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;  
a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and  
a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof,

the alignment member further including a pair of taper-segment-support fibers for engaging the fiber-optic-taper segment and holding the fiber-optic-taper segment partially wrapped around the at least one fiber-ring optical resonator, the taper-segment-support

fibers being positioned on the alignment member in corresponding taper-segment-support-fiber grooves thereof with the resonator-alignment groove therebetween, each taper-segment-support fiber comprising a transverse taper-segment-support segment integral with the taper-segment-support fiber between adjacent support-fiber segments, the fiber-optic-taper segment being supported by an outer circumference of the taper-segment-support segment, the taper-segment-support segment including paired axially-juxtaposed radially-extending radially-tapered transverse flanges, the fiber-optic-taper segment resting on the paired flanges.

56. A resonant optical filter assembly for an optical WDM system, comprising:
  - an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of

the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof,

the alignment member further including a pair of taper-segment-support fibers for engaging the fiber-optic-taper segment and holding the fiber-optic-taper segment partially wrapped around the at least one fiber-ring optical resonator, the taper-segment-support fibers being positioned on the alignment member in corresponding taper-segment-support-fiber grooves thereof with the resonator-alignment groove therebetween,

each taper-segment-support fiber comprising a transverse taper-segment-support segment integral with the taper-segment-support fiber between adjacent support-fiber segments, the fiber-optic-taper segment being supported by an outer circumference of the taper-segment-support segment,

each taper-segment-support fiber being provided with a de-localized-optical-mode suppressor on at least one of the adjacent segment thereof for suppressing optical modes of the taper-segment-support fiber.

57. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of

the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the resonant optical assembly including at least one fiber-ring optical resonator formed on a resonator optical fiber, the fiber-ring optical resonator including a transverse resonator segment integral with the resonator optical fiber between first and second segments of the resonator optical fiber, the resonator segment having a circumferential optical path length sufficiently different from a circumferential optical path length of an immediately adjacent portion of at least one of the first and second segments of the resonator optical fiber so as to enable the resonator segment to support at least one resonant optical mode near an outer circumferential surface of the resonator segment, the resonator optical fiber being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first and second transmission optical waveguides,

at least one of the first transmission optical waveguide and the second transmission optical waveguide being a transmission fiber-optic waveguide, the evanescent optical coupling segment of the transmission fiber-optic waveguide being a fiber-optic-taper segment, the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so that the fiber-optic-taper segment is partially wrapped around the at least one fiber-ring optical resonator near a portion of the outer circumference thereof,

the alignment member further including a pair of taper-segment-support fibers for engaging the fiber-optic-taper segment and holding the fiber-optic-taper segment partially wrapped around the at least one fiber-ring optical resonator, the taper-segment-support fibers being positioned on the alignment member in corresponding taper-segment-support-fiber grooves thereof with the resonator-alignment groove therebetween, each taper-segment-support fiber comprising a transverse taper-segment-support segment integral with the taper-segment-support fiber between adjacent support-fiber segments,



- the fiber-optic-taper segment being supported by an outer circumference of the taper-segment-support segment,
- each taper-segment-support fiber being provided with a hermetic carbon coating de-localized-optical-mode suppressor on at least one of the adjacent segment thereof for suppressing optical modes of the taper-segment-support fiber.
58. A resonant optical filter assembly for an optical WDM system, comprising:
- an alignment member, the alignment member including a first waveguide-alignment groove, a second waveguide-alignment groove, and a resonator-alignment groove;
  - a first transmission optical waveguide adapted for transmitting therethrough at least one of a plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the first transmission optical waveguide being positioned within the first waveguide-alignment groove and secured to the alignment member and having an evanescent optical coupling segment;
  - a second transmission optical waveguide adapted for transmitting therethrough at least one of the plurality of optical signals, each optical signal being carried by a respective waveguide optical mode corresponding to an optical channel of the WDM system, the second transmission optical waveguide being positioned within the second waveguide-alignment grooves and secured to the alignment member and having an evanescent optical coupling segment; and
  - a resonant optical assembly including at least one optical resonator, the resonant optical assembly supporting at least one resonant optical mode and being positioned within the resonator-alignment groove and secured to the alignment member so as to be evanescently optically coupled to the first transmission optical waveguide and the second transmission optical waveguide at the respective evanescent optical coupling segments thereof,
  - an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially resonant with at least one of the resonant optical modes being substantially transferred from the one to the other of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

an optical signal entering the resonant optical filter assembly through one of the first and second transmission optical waveguides and substantially non-resonant with any resonant optical mode supported by the resonant optical assembly substantially remaining within the one of the first and second transmission optical waveguides and leaving the resonant optical filter assembly therethrough,

the alignment member comprising

- a first alignment substrate including the first waveguide-alignment groove thereon, and
- a second alignment substrate positioned on and secured to the first alignment substrate, the second alignment substrate including at least one of the resonator-alignment groove and the second waveguide-alignment groove thereon,

the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.

59. A method for assembling a resonant optical filter assembly, comprising the steps of:
- positioning a first transmission optical waveguide within a first waveguide-alignment groove of an alignment member and securing the first transmission optical waveguide to the alignment member;
  - positioning a second transmission optical waveguide within a second waveguide-alignment groove of the alignment member and securing the second transmission optical waveguide to the alignment member; and
  - positioning a resonant optical assembly within a resonator-alignment groove of the alignment member, so that the resonant optical assembly is evanescently optically coupled to an evanescent optical coupling segment of the first transmission optical waveguide and evanescently optically coupled to an evanescent optical coupling segment of the second transmission optical waveguide, and securing the optical resonator to the alignment member,
- the first waveguide-alignment groove, the second waveguide-alignment groove, and the resonator-alignment groove being positioned on the alignment member so as to substantially reproducibly establish and substantially stably maintain evanescent optical

coupling between the first transmission optical waveguide and the resonant optical assembly and between the second transmission optical waveguide and the resonant optical assembly.


07/30/2001

**REMARKS**

Claims 13-59 have been added to the application and claim subject matter disclosed in the application as originally filed but not necessarily claimed therein.. Each of Claims 13-59 finds support in the drawings, written description, and/or claims of the application as originally filed.

Applicant awaits a first substantive Office Action on the application.

Respectfully submitted,



David S. Alavi  
Reg. No. 40,310  
dalavi@nu-world.com

3762 West 11th Avenue #408  
Eugene, OR 97402  
Phone: 541-346-4619

07/30/2001